

02/23/00

1685 U.S. PTO

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.
 00177/530809

Total Pages :

First Named Inventor or Application Identifier

Tomohiro OKUMURA et al.

Express Mail Label No.:

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
 Box Patent Application
 Washington, D.C. 20231

1. ☒ Fee Transmittal Form
 (Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages - 81]
 (preferred arrangement set forth below)
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 USC 113) [Total sheets - 18]
4. ☒ Oath or Declaration [Total Pages - 5]
 - a.1. ☐ Newly executed (original or copy)
 - a.2. ☒ Unexecuted
 - b. ☐ Copy from a prior application (37 CFR 1.63(d))
 (for continuation/divisional with Box 17 completed)
 [Note Box 5 below]
 - i. ☐ **DELETION OF INVENTOR(S)**
 Signed statement attached deleting inventor(s)
 named in the prior application, see 37 CFR
 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference
 (usable if Box 4b is checked)
 The entire disclosure of the prior application, from which
 a copy of the oath or declaration is supplied under Box
 4b, is considered as being part of the disclosure of the
 accompanying application and is hereby incorporated by
 reference therein.

6. Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Statement
 (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
 (when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449
☐ Copies of IDS Citations
12. ☒ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
 (Should be specifically itemized)
14. ☐ Small Entity Statement(s)
15. ☒ Statement filed in prior application, Status still proper and desired
16. ☒ Certified Copy of Priority Document(s)
 (if foreign priority is claimed)
16. ☐ Other

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior Application No.

18. CORRESPONDENCE ADDRESS

WENDEROTH, LIND & PONACK
 2033 "K" Street, N.W.
 Suite 800
 Washington, D.C. 20006
 Phone: (202) 721-8200
 Fax: (202) 721-8250

February 23, 2000

02/23/00
 09/51398
 Jc-564 U.S. PTO

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of :
Tomohiro OKUMURA et al. : **Attn: APPLICATION BRANCH**
Serial No. NEW : Docket No. 00177/530809
Filed February 23, 2000 :
**PLASMA PROCESSING METHOD AND
APPARATUS**

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents,
Washington, DC 20231

Sir:

Please amend the above-identified application as follows.

In the Claims:

Kindly amend claim 18 as follows.

Claim 18, line 2, delete "or 15".

Kindly add new claim 55 as follows.

55. A plasma processing apparatus according to Claim 15, wherein the plasma has a groove depth of not less than 5 mm.

REMARKS

The above claim amendments are presented in order to remove multiple claim dependency, so as to reduce the required filing fee.

Respectfully submitted,

Tomohiro OKUMURA et al.

By Wan as checky # 33,367
for Charles R. Watts
Registration No. 33,142
Attorney for Applicants

CRW/asd
Washington, D.C.
Telephone (202) 721-8200
Facsimile (202) 721-8250
February 23, 2000

SPECIFICATION

TITLE OF THE INVENTION

Plasma Processing Method and Apparatus

5 BACKGROUND OF THE INVENTION

The present invention relates to plasma processing methods such as dry etching, sputtering, and plasma CVD, as well as apparatuses therefor, to be used for manufacture of semiconductor or other electron devices and micromachines. More particularly, the present invention relates to plasma processing method and apparatus for use of plasma excited with high-frequency power of VHF or UHF band.

The present invention further relates to a matching box for plasma processing apparatus to be used for impedance matching in supplying high-frequency power of VHF band, in particular, to a counter electrode for plasma excitation or to an antenna, and relates to plasma processing method and apparatus using plasma excited with the high-frequency power of VHF band.

Whereas Japanese Laid-Open Patent Publication No. 8-83696 describes that use of high-density plasma is important in order to meet the trend toward microstructures of semiconductors and other electron devices, low electron temperature plasma has recently been receiving attention by virtue of its high electron density and low electron

temperature.

In the case where a gas having a high negativity, i.e., a gas that tends to generate negative ions, such as Cl_2 , SF_6 , is formed into plasma, when the electron temperature becomes about 3 eV or lower, larger amounts of negative ions are generated than with higher electron temperatures. Taking advantage of this phenomenon makes it possible to prevent etching configuration abnormalities, so-called notch, which may occur when positive charges are accumulated at the bottom of micro-patterns due to excessive incidence of positive ions. This allows etching of extremely micro patterns to be achieved with high precision.

Also, in the case where a gas containing carbon and fluorine, such as C_xF_y or $\text{C}_x\text{H}_y\text{F}_z$ (where x, y, z are natural numbers), which is generally used for etching of insulating films such as silicon oxide, is formed into plasma, when the electron temperature becomes about 3 eV or lower, gas dissociation is suppressed more than with higher electron temperatures, where, in particular, generation of F atoms, F radicals and the like is suppressed. Because F atoms, F radicals and the like are higher in the rate of silicon etching, insulating film etching can be carried out at larger selection ratios to silicon etching the more with lower electron temperatures.

Also, when the electron temperature becomes 3 eV or lower, ion temperature and plasma potential also becomes lower, so that ion damage to the substrate in plasma CVD can be reduced.

5 As a technique capable of generating plasma having low electron temperature, plasma sources using high-frequency power of VHF band or UHF band are now receiving attention.

Fig. 15 is a sectional view of a dual-frequency
10 excitation parallel-flat plate type plasma processing apparatus. Referring to Fig. 15, while interior of a vacuum chamber 201 is maintained to a specified pressure by introducing a specified gas from a gas supply unit 202 into the vacuum chamber 201 and simultaneously performing
15 evacuation by a pump 203 as an evacuating device, a high-frequency power of 100 MHz is supplied to a counter electrode 205 by a counter-electrode-use-high-frequency power supply 204. Then, plasma is generated in the vacuum chamber 201, where plasma processing such as etching,
20 deposition, and surface reforming can be carried out on a substrate 207 placed on a substrate electrode 206. In this case, as shown in Fig. 15, by supplying high-frequency power also to the substrate electrode 206 by a substrate-electrode-use-high-frequency power supply 208, ion energy
25 that reaches the substrate 207 can be controlled. In

addition, the counter electrode 205 is insulated from the vacuum chamber 201 by an insulating ring 211.

Fig. 16 is a sectional view of a plasma processing apparatus which we have already proposed and which has an antenna type plasma source mounted thereon. Referring to Fig. 16, while interior of a vacuum chamber 301 is maintained to a specified pressure by introducing a specified gas from a gas supply unit 302 into the vacuum chamber 301 and simultaneously performing evacuation by a pump 303 as an evacuating device, a high-frequency power of 100 MHz is supplied to a spiral antenna 313 on a dielectric window 314 by an antenna-use-high-frequency power supply 312. Then, plasma is generated in the vacuum chamber 301 by electromagnetic waves radiated into the vacuum chamber 301, where plasma processing such as etching, deposition, and surface reforming can be carried out on a substrate 307 placed on a substrate electrode 306. In this case, as shown in Fig. 16, by supplying high-frequency power also to the substrate electrode 306 by a substrate-electrode-use-high-frequency power supply 308, ion energy that reaches the substrate 307 can be controlled.

However, there has been an issue that the conventional methods shown in Figs. 15 and 16 have difficulty in obtaining uniformity of plasma.

Fig. 17 shows results of measuring ion saturation

current density at a position 20 mm just above the substrate 207 in the plasma processing apparatus of Fig. 15. Conditions for plasma generation are gas type of Cl_2 and gas flow rate of 100 sccm, a pressure of 1 Pa, and a high-frequency power of 2 kW. It can be understood from Fig. 17 that plasma density is higher in peripheral regions.

Fig. 18 shows results of measuring ion saturation current density at a position 20 mm just above the substrate 307 in the plasma processing apparatus of Fig. 16. Conditions for plasma generation are gas type of Cl_2 and gas flow rate of 100 sccm, a pressure of 1 Pa, and a high-frequency power of 2 kW. It can be understood from Fig. 18 that plasma density is higher in peripheral regions.

Such nonuniformity of plasma is phenomenon that could not be seen with the frequency of the high-frequency power of 50 MHz or less. Whereas the 50 MHz or higher high-frequency power needs to be used in order to lower the electron temperature of plasma, there are produced, in this frequency band, not only an advantage that plasma is generated by the counter electrode or antenna being capacitively or inductively coupled to the plasma, but also an advantage that plasma is generated by electromagnetic waves, which are radiated from the counter electrode or antenna, propagating on the surface of the plasma. In peripheral regions of the vacuum chamber, which serve as

reflecting surfaces for the electromagnetic waves that have propagated on the surface of the plasma, stronger electric fields are developed so that thick plasma is generated.

Also, as described above, in the case where a gas
5 having a high negativity, i.e., a gas that tends to generate negative ions, such as Cl_2 , SF_6 , is formed into plasma, when the electron temperature becomes about 3 eV or lower, larger amounts of negative ions are generated than with higher electron temperatures. Taking advantage of
10 this phenomenon makes it possible to prevent a phenomenon that perpendicularity of the incident angle of ions onto the substrate worsens when positive charges are accumulated at the bottom of micro-patterns due to excessive incidence of positive ions. This allows etching of extremely micro
15 patterns to be achieved with high precision. Besides, that is an expectation for process improvement making use of the high reactivity of negative ions.

Also, in the case where a gas containing carbon and fluorine, such as C_xF_y or $\text{C}_x\text{H}_y\text{F}_z$ (where x, y, z are
20 natural numbers), which is generally used for etching of insulating films such as silicon oxide, is formed into plasma, when the electron temperature becomes about 3 eV or lower, gas dissociation is suppressed more than with higher electron temperatures, where, in particular, generation of
25 F atoms, F radicals and the like is suppressed. Because F

atoms, F radicals and the like are higher in the rate of silicon etching, insulating film etching can be carried out at larger selection ratios to silicon etching the more with lower electron temperatures.

5 Also, when the electron temperature becomes 3 eV or lower, ion temperature and plasma potential also become lower, so that ion damage to the substrate in plasma CVD can be reduced.

10 It is plasma sources using high-frequency power of VHF band that is currently receiving attention as a technique capable of generating plasma low in electron temperature and capable of generating plasma superior in ignitability.

15 Fig. 24 is a sectional view of a dual-frequency excitation parallel-flat plate type plasma processing apparatus. Referring to Fig. 24, while interior of a vacuum chamber 401 is maintained to a specified pressure by introducing a specified gas from a gas supply unit 402 into the vacuum chamber 401 and simultaneously performing
20 evacuation by a pump 403 as an evacuating device, a high-frequency power of 100 MHz is supplied to a counter electrode 407 via a matching box 405 and a high-frequency coupling device (mount) 406 by a counter-electrode-use-high-frequency power supply 404. Then, plasma is generated
25 in the vacuum chamber 401, where plasma processing such as

etching, deposition, and surface reforming can be carried out on a substrate 409 placed on a substrate electrode 408. In this case, as shown in Fig. 24, by supplying high-frequency power also to the substrate electrode 408 by a substrate-electrode-use-high-frequency power supply 410, ion energy that reaches the substrate 409 can be controlled. In addition, the counter electrode 407 is insulated from the vacuum chamber 401 by an insulating ring 411. The matching box 405 comprises a high-frequency input terminal 412, a first variable capacitor 413, a high-frequency output terminal 414, a second variable capacitor 415, a first motor 416, a second motor 417, and a motor control circuit 418.

However, there has been an issue that the conventional method shown in Fig. 24 has difficulty in obtaining uniformity of plasma.

Fig. 25 shows results of measuring ion saturation current density at a position 20 mm just above the substrate 409 in the plasma processing apparatus of Fig. 24. Conditions for plasma generation are gas type of Cl_2 and gas flow rate of 100 sccm, a pressure of 2 Pa and a high-frequency power of 1 kW. Also, as shown in Fig. 24, the second variable capacitor 415 is disposed on one side of the measuring position in Fig. 25. It can be understood from Fig. 25 that plasma density is higher on one side of

the measuring position, i.e., just below the second variable capacitor 415.

Such nonuniformity of plasma is phenomenon that could not be seen with the frequency of the high-frequency power of 50 MHz or less. Whereas the 50 MHz or higher high-frequency power needs to be used in order to lower the electron temperature of plasma, there develops, in this frequency band, a potential distribution in the counter electrode 407. It can be deduced that this potential distribution, affected by the placement of the second variable capacitor 415 within the matching box 405, acts to strengthen the electric fields just below the second variable capacitor 415, resulting in nonuniformity of plasma.

Such a phenomenon could be seen with such an arrangement as shown in Fig. 26 in which a spiral antenna 420 is used instead of the counter electrode 407. In the prior art example shown in Fig. 26, a dielectric window 421 is used.

SUMMARY OF THE INVENTION

In view of these issues of the prior art, an object of the present invention is to provide plasma processing method and apparatus, as well as a matching box for plasma processing apparatus, capable of generating uniform plasma.

In order to achieve the above object, the present invention has the following constitutions.

In accomplishing these and other aspects, according to a first aspect of the present invention, there is provided a plasma processing method for generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode within the vacuum chamber, the method comprising:

generating the plasma by supplying a high-frequency power having a frequency of 50 MHz to 3 GHz to a counter electrode provided opposite to the substrate while interior of the vacuum chamber is controlled to a specified pressure by introducing gas into the vacuum chamber and, simultaneously therewith, evacuating the interior of the vacuum chamber; and

processing the substrate by using the generated plasma while plasma distribution of the plasma on the substrate is controlled by an annular, groove-like plasma trap provided opposite to the substrate.

According to a second aspect of the present invention, there is provided a plasma processing method for generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode within the vacuum chamber, the method comprising:

generating the plasma by radiating electromagnetic

waves into the vacuum chamber via a dielectric window provided opposite to the substrate by supplying a high-frequency power having a frequency of 50 MHz to 3 GHz to an antenna while interior of the vacuum chamber is controlled to a specified pressure by introducing gas into the vacuum chamber and, simultaneously therewith, evacuating the interior of the vacuum chamber; and

processing the substrate by using the generated plasma while plasma distribution of the plasma on the substrate is controlled by an annular, groove-like plasma trap provided opposite to the substrate.

According to a third aspect of the present invention, there is provided a plasma processing method according to the first aspect, wherein the substrate is processed while a portion surrounded by the plasma trap out of a surface forming an inner wall surface of the vacuum chamber and opposing the substrate has an area 0.5 to 2.5 times that of the substrate.

According to a fourth aspect of the present invention, there is provided a plasma processing method according to the first aspect, wherein the substrate is processed while the plasma trap has a groove width of 3 mm to 50 mm.

According to a fifth aspect of the present invention, there is provided a plasma processing method

according to the first aspect, wherein the substrate is processed while the plasma has a groove depth of not less than 5 mm.

According to a sixth aspect of the present invention, there is provided a plasma processing method according to the first aspect, wherein the substrate is processed while the plasma trap is provided in the counter electrode.

According to a seventh aspect of the present invention, there is provided a plasma processing method according to the first aspect, wherein the plasma is generated while the plasma trap is provided outside an insulating ring for insulating the vacuum chamber and the counter electrode from each other.

According to an eighth aspect of the present invention, there is provided a plasma processing method according to the first aspect, wherein the plasma is generated while the plasma trap is provided between the counter electrode and an insulating ring for insulating the vacuum chamber and the counter electrode from each other.

According to a ninth aspect of the present invention, there is provided a plasma processing method according to the first aspect, wherein the plasma is generated while the plasma trap is provided between the vacuum chamber and an insulating ring for insulating the

vacuum chamber and the counter electrode from each other.

According to a 10th aspect of the present invention, there is provided a plasma processing method according to the second aspect, wherein the plasma is
5 generated while the plasma trap is provided in the dielectric window.

According to an 11th aspect of the present invention, there is provided a plasma processing method according to the second aspect, wherein the plasma is
10 generated while the plasma trap is provided outside the dielectric window.

According to a 12th aspect of the present invention, there is provided a plasma processing method according to the second aspect, wherein the plasma is
15 generated while the plasma trap is provided between the vacuum chamber and the dielectric window.

According to a 13th aspect of the present invention, there is provided a plasma processing method according to the first aspect, wherein the plasma is
20 generated while DC magnetic fields are absent within the vacuum chamber.

According to a 14th aspect of the present invention, there is provided a plasma processing apparatus comprising:

25 a vacuum chamber;

a gas supply unit for supplying gas into the vacuum chamber;

an evacuating device for evacuating interior of the vacuum chamber;

5 a substrate electrode for placing thereon a substrate within the vacuum chamber;

a counter electrode provided opposite to the substrate electrode;

high-frequency power supply capable of supplying
10 a high-frequency power having a frequency of 50 MHz to 3 GHz to the counter electrode; and

an annular, groove-like plasma trap provided opposite to the substrate.

According to a 15th aspect of the present
15 invention, there is provided a plasma processing apparatus comprising:

a vacuum chamber;

a gas supply unit for supplying gas into the vacuum chamber;

20 an evacuating device for evacuating interior of the vacuum chamber;

a substrate electrode for placing thereon a substrate within the vacuum chamber;

a dielectric window provided opposite to the
25 substrate electrode;

an antenna for radiating electromagnetic waves into the vacuum chamber via the dielectric window;

high-frequency power supply capable of supplying a high-frequency power having a frequency of 50 MHz to 3
5 GHz to the antenna; and

an annular, groove-like plasma trap provided opposite to the substrate.

According to a 16th aspect of the present invention, there is provided a plasma processing apparatus
10 according to the 14th aspect, wherein a portion surrounded by the plasma trap out of a surface forming an inner wall surface of the vacuum chamber and opposing the substrate has an area 0.5 to 2.5 times that of the substrate.

According to a 17th aspect of the present
15 invention, there is provided a plasma processing apparatus according to the 14th aspect, wherein the plasma trap has a groove width of 3 mm to 50 mm.

According to a 18th aspect of the present invention, there is provided a plasma processing apparatus
20 according to the 14th or 15th aspect, wherein the plasma has a groove depth of not less than 5 mm.

According to a 19th aspect of the present invention, there is provided a plasma processing apparatus according to the 14th aspect, wherein the plasma trap is
25 provided in the counter electrode.

According to a 20th aspect of the present invention, there is provided a plasma processing apparatus according to the 14th aspect, wherein the plasma trap is provided in an insulating ring for insulating the vacuum chamber and the counter electrode from each other.

According to a 21st aspect of the present invention, there is provided a plasma processing apparatus according to the 14th aspect, wherein the plasma trap is provided outside an insulating ring for insulating the vacuum chamber and the counter electrode from each other.

According to a 22nd aspect of the present invention, there is provided a plasma processing apparatus according to the 14th aspect, wherein the plasma trap is provided between the counter electrode and an insulating ring for insulating the vacuum chamber and the counter electrode from each other.

According to a 23rd aspect of the present invention, there is provided a plasma processing apparatus according to the 14th aspect, wherein the plasma trap is provided between the vacuum chamber and an insulating ring for insulating the vacuum chamber and the counter electrode from each other.

According to a 24th aspect of the present invention, there is provided a plasma processing apparatus according to the 15th aspect, wherein the plasma trap is

provided in the dielectric window.

According to a 25th aspect of the present invention, there is provided a plasma processing apparatus according to the 15th aspect, wherein the plasma trap is
5 provided outside the dielectric window.

According to a 26th aspect of the present invention, there is provided a plasma processing apparatus according to the 15th aspect, wherein the plasma trap is provided between the vacuum chamber and the dielectric
10 window.

According to a 27th aspect of the present invention, there is provided a plasma processing apparatus according to the 14th aspect, wherein no coil or permanent magnet for applying DC magnetic fields is provided within
15 the vacuum chamber.

According to a 28th aspect of the present invention, there is provided a plasma processing apparatus according to the first aspect, further comprising a matching box for use in the plasma processing apparatus and
20 for taking impedance matching in supplying high-frequency power to a load, the matching box comprising:

a high-frequency input terminal;

a first reactive element having one end connected to the high-frequency input terminal and the other end
25 connected to a matching box casing;

a high-frequency output terminal; and
a second reactive element having one end connected to the high-frequency input terminal and the other end connected to the high-frequency output terminal,

5 wherein the second reactive element and the high-frequency output terminal are so arranged that the second reactive element is located on a straight line passing through a center axis of the high-frequency output terminal.

According to a 29th aspect of the present
10 invention, there is provided a plasma processing apparatus according to the 28th aspect, wherein the first reactive element and the second reactive element are capacitors, respectively.

According to a 30th aspect of the present
15 invention, there is provided a matching box for use in a plasma processing apparatus and for taking impedance matching in supplying high-frequency power to a load, the matching box comprising:

a high-frequency input terminal;
20 a first reactive element having one end connected to the high-frequency input terminal and the other end connected to a matching box casing;
a high-frequency output terminal; and
a second reactive element having one end
25 connected to the high-frequency input terminal and the

other end connected to the high-frequency output terminal,

wherein the second reactive element and the high-frequency output terminal are so arranged that the second reactive element is located on a straight line passing through a center axis of the high-frequency output terminal.

According to a 31st aspect of the present invention, there is provided a matching box for a plasma processing apparatus according to the 30th aspect, wherein the second reactive element and the high-frequency output terminal are so arranged that a straight line passing through a center axis of the second reactive element and a straight line passing through the center axis of the high-frequency output terminal are generally coincident with each other.

According to a 32nd aspect of the present invention, there is provided a matching box for a plasma processing apparatus according to the 30th aspect, wherein the first reactive element and the second reactive element are capacitors, respectively.

According to a 33rd aspect of the present invention, there is provided a matching box for a plasma processing apparatus according to the 30th aspect, wherein the first reactive element and the second reactive element are so arranged that a straight line passing through a center axis of the second reactive element and a straight

line passing through a center axis of the first reactive element are generally coincident with each other.

According to a 34th aspect of the present invention, there is provided a matching box for a plasma processing apparatus according to the 30th aspect, wherein
5 the high-frequency output terminal is the other end itself of the second reactive element.

According to a 35th aspect of the present invention, there is provided a plasma processing method for
10 generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode within the vacuum chamber, the method comprising:

so arranging a straight line passing through a center axis of the high-frequency coupling device, a
15 straight line passing through a center axis of the counter electrode or antenna, and a straight line passing through a center axis of the substrate as to be generally coincident together;

controlling interior of the vacuum chamber to a
20 specified pressure by introducing a gas into the vacuum chamber and, simultaneously therewith, exhausting the interior of the vacuum chamber;

generating the plasma by applying a high-frequency power having a frequency of 50 MHz to 300 MHz to
25 a counter electrode or antenna provided opposite to the

substrate via the matching box as defined in the 30th aspect and a high-frequency coupling device provided to connect a high-frequency output terminal of the matching box and the counter electrode or antenna to each other; and

5 processing the substrate by using the generated plasma.

 According to a 36th aspect of the present invention, there is provided a plasma processing method according to the 35th aspect, further comprising: before
10 controlling the interior of the vacuum chamber to the specified pressure,

 so arranging a straight line passing through a center axis of the high-frequency output terminal and a straight line passing through the center axis of the high-
15 frequency coupling device as to be generally coincident with each other,

 wherein the plasma is generated with the straight line passing through the center axis of the high-frequency output terminal and the straight line passing through the
20 center axis of the high-frequency coupling device being generally coincident with each other.

 According to a 37th aspect of the present invention, there is provided a plasma processing method according to the 35th aspect, further comprising: before
25 controlling the interior of the vacuum chamber to the

specified pressure,

so arranging the first reactive element and the second reactive element that a straight line passing through a center axis of the second reactive element and a straight line passing through a center axis of the first reactive element are generally coincident with each other,

wherein the plasma is generated with the straight line passing through the center axis of the second reactive element and the straight line passing through the center axis of the first reactive element being generally coincident with each other.

According to a 38th aspect of the present invention, there is provided a plasma processing method according to the 35th aspect, comprising: before controlling the interior of the vacuum chamber to the specified pressure,

arranging the high-frequency output terminal so as to be the other end itself of the second reactive element,

wherein the plasma is generated with the high-frequency output terminal being the other end itself of the second reactive element.

According to a 39th aspect of the present invention, there is provided a plasma processing method according to the 35th aspect, comprising: before controlling

the interior of the vacuum chamber to the specified pressure,

arranging substantial distance from the other end of the second reactive element to the counter electrode or antenna to be not more than $1/10$ of wavelength of the high-frequency power,

wherein the plasma is generated with the substantial distance from the other end of the second reactive element to the counter electrode or antenna being not more than $1/10$ of wavelength of the high-frequency power.

According to a 40th aspect of the present invention, there is provided a plasma processing method for generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode within the vacuum chamber, the method comprising:

so arranging a straight line passing through a center axis of the high-frequency coupling device, a straight line passing through a center axis of the counter electrode or antenna, and a straight line passing through a center axis of the substrate as to be generally coincident together;

controlling interior of the vacuum chamber to a specified pressure by introducing a gas into the vacuum chamber and, simultaneously therewith, exhausting the

interior of the vacuum chamber;

generating the plasma by applying a high-frequency power having a frequency of 50 MHz to 300 MHz to a counter electrode or antenna provided opposite to the substrate via the matching box as defined in the 30th aspect and a high-frequency coupling device provided to connect a high-frequency output terminal of the matching box and the counter electrode or antenna to each other; and

processing the substrate by using the generated plasma.

According to a 41st aspect of the present invention, there is provided a plasma processing method according to the 40th aspect, further comprising: before controlling the interior of the vacuum chamber to the specified pressure,

so arranging a straight line passing through a center axis of the high-frequency output terminal and a straight line passing through the center axis of the high-frequency coupling device as to be generally coincident with each other,

wherein the plasma is generated with the straight line passing through the center axis of the high-frequency output terminal and the straight line passing through the center axis of the high-frequency coupling device being generally coincident with each other.

According to a 42nd aspect of the present invention, there is provided a plasma processing method according to the 40th aspect, further comprising: before controlling the interior of the vacuum chamber to the specified pressure,

so arranging the first variable capacitor and the second variable capacitor that a straight line passing through a center axis of the second variable capacitor and a straight line passing through a center axis of the first variable capacitor are generally coincident with each other,

wherein the plasma is generated with the straight line passing through the center axis of the second variable capacitor and the straight line passing through the center axis of the first variable capacitor being generally coincident with each other.

According to a 43rd aspect of the present invention, there is provided a plasma processing method according to the 40th aspect, comprising: before controlling the interior of the vacuum chamber to the specified pressure,

arranging the high-frequency output terminal so as to be the other end itself of the second reactive element,

wherein the plasma is generated with the high-frequency output terminal being the other end itself of the

second variable capacitor.

According to a 44th aspect of the present invention, there is provided a plasma processing method according to the 40th aspect, further comprising: before
5 controlling the interior of the vacuum chamber to the specified pressure,

arranging substantial distance from the other end of the second variable capacitor to the counter electrode or antenna to be not more than $1/10$ of wavelength of the
10 high-frequency power,

wherein the plasma is generated with the substantial distance from the other end of the second variable capacitor to the counter electrode or antenna to be not more than $1/10$ of wavelength of the high-frequency
15 power.

According to a 45th aspect of the present invention, there is provided a plasma processing apparatus comprising:

a vacuum chamber;
20 a gas supply unit for supplying gas into the vacuum chamber;

an evacuating device for evacuating interior of the vacuum chamber;

a substrate electrode for placing thereon a
25 substrate within the vacuum chamber;

a counter electrode or an antenna provided opposite to the substrate electrode;

high-frequency power supply capable of supplying a high-frequency power having a frequency of 50 MHz to 300
5 MHz to the counter electrode or antenna;

the matching box as defined in the 30th aspect;
and

a high-frequency coupling device for connecting the high-frequency output terminal of the matching box and
10 the counter electrode or antenna to each other,

wherein a straight line passing through a center axis of the high-frequency coupling device, a straight line passing through a center axis of the counter electrode or antenna, and a straight line passing through a center axis
15 of the substrate are so arranged as to be generally coincident together.

According to a 46th aspect of the present invention, there is provided a plasma processing apparatus according to the 45th aspect, wherein a straight line
20 passing through a center axis of the high-frequency output terminal and a straight line passing through the center axis of the high-frequency coupling device are so arranged as to be generally coincident with each other.

According to a 47th aspect of the present
25 invention, there is provided a plasma processing apparatus

according to the 45th aspect, wherein the first reactive element and the second reactive element are so arranged that a straight line passing through a center axis of the second reactive element and a straight line passing through
5 a center axis of the first reactive element are generally coincident with each other.

According to a 48th aspect of the present invention, there is provided a plasma processing apparatus according to the 45th aspect, wherein the high-frequency
10 output terminal is the other end itself of the second reactive element.

According to a 49th aspect of the present invention, there is provided a plasma processing apparatus according to the 45th aspect, wherein substantial distance
15 from the other end of the second reactive element to the counter electrode or antenna is not more than $1/10$ of wavelength of the high-frequency power.

According to a 50th aspect of the present invention, there is provided a plasma processing apparatus
20 comprising:

a vacuum chamber;

a gas supply unit for supplying gas into the vacuum chamber;

an evacuating device for evacuating interior of
25 the vacuum chamber;

... a substrate electrode for placing thereon a substrate within the vacuum chamber;

a counter electrode or an antenna provided opposite to the substrate electrode;

5 high-frequency power supply capable of supplying a high-frequency power having a frequency of 50 MHz to 300 MHz to the counter electrode or antenna;

the matching box as defined in the 30th aspect; and

10 a high-frequency coupling device for connecting the high-frequency output terminal of the matching box and the counter electrode or antenna to each other,

wherein a straight line passing through a center axis of the high-frequency coupling device, a straight line
15 passing through a center axis of the counter electrode or antenna, and a straight line passing through a center axis of the substrate are so arranged as to be generally coincident together.

According to a 51st aspect of the present
20 invention, there is provided a plasma processing apparatus according to the 50th aspect, wherein the plasma is generated while the straight line passing through the center axis of the high-frequency output terminal and the straight line passing through the center axis of the high-
25 frequency coupling device are so arranged as to be generally

coincident with each other.

According to a 52nd aspect of the present invention, there is provided a plasma processing apparatus according to the 50th aspect, wherein a first variable capacitor and a second variable capacitor are so arranged that a straight line passing through a center axis of the second variable capacitor and a straight line passing through a center axis of the first variable capacitor are generally coincident with each other.

According to a 53rd aspect of the present invention, there is provided a plasma processing apparatus according to the 50th aspect, wherein the high-frequency output terminal is the other end itself of the second variable capacitor.

According to a 54th aspect of the present invention, there is provided a plasma processing apparatus according to the 50th aspect, wherein substantial distance from the other end of the second variable capacitor to the counter electrode or antenna is not more than $1/10$ of wavelength of the high-frequency power.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other aspects and features of the present invention will become clear from the following description taken in conjunction with the preferred embodiments thereof with reference to the accompanying

drawings, in which:

Fig. 1A is a sectional view showing the constitution of a plasma processing apparatus employed in a first embodiment of the present invention;

5 Fig. 1B is a plan view of plasma trap of the plasma processing apparatus of Fig. 1A;

Fig. 2 is a chart showing measuring results of ion saturation current density in the first embodiment of the present invention;

10 Fig. 3 is a sectional view showing the constitution of a plasma processing apparatus employed in a second embodiment of the present invention;

Fig. 4 is a sectional view showing the constitution of a plasma processing apparatus employed in a
15 third embodiment of the present invention;

Fig. 5 is a sectional view showing the constitution of a plasma processing apparatus employed in a fourth embodiment of the present invention;

Fig. 6 is a sectional view showing the
20 constitution of a plasma processing apparatus employed in a fifth embodiment of the present invention;

Fig. 7 is a sectional view showing the constitution of a plasma processing apparatus employed in a sixth embodiment of the present invention;

25 Fig. 8 is a sectional view showing the

constitution of a plasma processing apparatus employed in a seventh embodiment of the present invention;

Fig. 9 is a chart showing measuring results of ion saturation current density in the seventh embodiment of the present invention;

Fig. 10 is a sectional view showing the constitution of a plasma processing apparatus employed in an eighth embodiment of the present invention;

Fig. 11 is a sectional view showing the constitution of a plasma processing apparatus employed in a ninth embodiment of the present invention;

Fig. 12 is a sectional view showing the constitution of a plasma processing apparatus employed in another embodiment of the present invention;

Fig. 13 is a sectional view showing the constitution of a plasma processing apparatus employed in another embodiment of the present invention;

Fig. 14 is a plan view of constitution of plasma traps employed in another embodiment of the present invention;

Fig. 15 is a sectional view showing the constitution of a plasma processing apparatus employed in a prior art example;

Fig. 16 is a sectional view showing the constitution of a plasma processing apparatus employed in a

prior art example;

Fig. 17 is a chart showing measuring results of ion saturation current density in a prior art example;

Fig. 18 is a chart showing measuring results of ion saturation current density in a prior art example;

Fig. 19 is a sectional view showing the constitution of a plasma processing apparatus employed in a tenth embodiment of the present invention;

Fig. 20 is a chart showing measuring results of ion saturation current density in the tenth embodiment of the present invention;

Fig. 21 is a sectional view showing the constitution of a plasma processing apparatus employed in an eleventh embodiment of the present invention;

Fig. 22 is a sectional view showing the constitution of a plasma processing apparatus employed in a twelfth embodiment of the present invention;

Fig. 23 is a sectional view showing the constitution of a plasma processing apparatus employed in a thirteenth embodiment of the present invention;

Fig. 24 is a sectional view showing the constitution of a plasma processing apparatus employed in a prior art example;

Fig. 25 is a chart showing measuring results of ion saturation current density in the prior art example;

Fig. 26 is a sectional view showing the constitution of a plasma processing apparatus employed in another prior art example;

Fig. 27 is a sectional view showing the constitution of a plasma processing apparatus employed in a
5 modification of the third embodiment of the present invention;

Fig. 28 is a sectional view showing the constitution of a plasma processing apparatus employed in a
10 modification of the eighth embodiment of the present invention;

Fig. 29 is a sectional view showing the constitution of a plasma processing apparatus where the plasma processing apparatus in the tenth embodiment of the
15 present invention in Fig. 19 and the plasma processing apparatus in the modification of the third embodiment of the present invention in Fig. 27 are combined with each other; and

Fig. 30 is a sectional view showing the constitution of a plasma processing apparatus where the
20 plasma processing apparatus in the eleventh embodiment of the present invention in Fig. 21 and the plasma processing apparatus in the modification of the eighth embodiment of the present invention in Fig. 28 are combined with each
25 other.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Before the description of the present invention proceeds, it is to be noted that like parts are designated by like reference numerals throughout the accompanying drawings.

Hereinbelow, embodiments according to the present invention are described in detail with reference to the accompanying drawings.

A first embodiment of the present invention is described below with reference to Figs. 1A, 1B, and 2.

Fig. 1A shows a sectional view of a plasma processing apparatus employed in the first embodiment of the present invention. Referring to Fig. 1A, while interior of a vacuum chamber 1 is maintained to a specified pressure by introducing a specified gas from a gas supply unit 2 into the vacuum chamber 1 and simultaneously performing evacuation by a pump 3 as an evacuating device, a high-frequency power of 100 MHz is supplied to a counter electrode 5 by a counter-electrode-use-high-frequency power supply 4. Then, plasma is generated in the vacuum chamber 1, where plasma processing such as etching, deposition, and surface reforming can be carried out on a substrate 7 placed on a substrate electrode 6. A substrate-electrode-use-high-frequency power supply 8 for supplying high-frequency power to the substrate electrode 6 is also

provided, so that ion energy that reaches the substrate 7 can be controlled. Also, an annular, groove-like plasma trap 9 shown in Figs. 1A and 1B is provided opposite to the substrate 7, making it possible to process the substrate 7 while the plasma distribution on the substrate 7 is controlled. The plasma trap 9 is provided in the counter electrode 5. Out of surfaces forming inner wall surfaces of the vacuum chamber 1 and opposing to the substrate 7, a portion 10 (cross hatched portion) surrounded by the plasma trap 9 has an area 0.8 time that of the substrate 7, as one example. Also, the groove width of the plasma trap 9 is 10 mm, and the groove depth of the plasma 9 is 15 mm, as one example. In addition, the counter electrode 5 is insulated from the vacuum chamber 1 by an insulating ring 11.

Fig. 2 shows measuring results of ion saturation current density at a position 20 mm just above the substrate 7. Conditions for plasma generation are gas type of Cl_2 and gas flow rate of 100 sccm, a pressure of 1 Pa, and a high-frequency power of 2 kW, as one example. It can be understood from Fig. 2 that the tendency that plasma would be richer in peripheral regions as shown in Fig. 17 is suppressed, and that uniform plasma is generated.

The reason why the uniformity of plasma is improved like this as compared with the plasma processing apparatus shown in Fig. 15 of the prior art example could

be considered as follows. Electromagnetic waves radiated from the counter electrode 5 are intensified by the plasma trap 9. Also, since plasma of low electron temperature tends to cause hollow cathode discharge, high density plasma (hollow cathode discharge) is more likely to be generated by the plasma trap 9 surrounded by the solid surfaces. Accordingly, in the vacuum chamber 1, plasma density becomes the highest at the plasma trap 9, and through transport of plasma to vicinities of the substrate 7 by diffusion, uniform plasma can be obtained.

In addition, the hollow cathode discharge is as described below. Generally, because a solid surface in contact with plasma is negatively charged due to differences in thermal motion velocity between electrons and ions, DC electric fields that repel electrons from the solid surface are generated on the solid surface. In a space surrounded by solid surfaces, as in the plasma trap 9 illustrated in the first embodiment of the present invention, the probability at which electrons collide with the solid surfaces is lowered by the presence of the DC electric fields, making the life of the electrons to be prolonged. As a result, high-density plasma is generated in the plasma trap 9. Such a discharge is referred to as hollow cathode discharge.

The first embodiment of the present invention has

been described above on the case where the plasma trap 9 is provided in the counter electrode 5. In this case, however, there is a possibility that a self-bias voltage developed to the counter electrode 5 causes high-density ions present in the plasma trap 9 to collide with the counter electrode 5 at high energy so that sputtering of the counter electrode 5 may occur. The sputtering of the counter electrode 5 may cause shortened life of the counter electrode 5 or mixing of impurities into the substrate 7, thus being undesirable. This can be avoided by providing the plasma trap in portions other than the counter electrode 5. For example, the plasma trap 9 may be provided in the insulating ring 11 as shown in a second embodiment of Fig. 3. Also, the plasma trap 9 may be provided outside the insulating ring 11, that is, in a metallic upper wall 1a of the vacuum chamber 1 as shown in a third embodiment of Fig. 4. Further, also when the plasma trap 9 is provided between the counter electrode 5 and the insulating ring 11 as shown in a fourth embodiment of Fig. 5 or a fifth embodiment of Fig. 6, improvement can be attained more or less. Furthermore, the plasma trap 9 may be provided between the upper wall 1a of the vacuum chamber 1 and the insulating ring 11 as shown in a sixth embodiment of Fig. 7.

In Fig. 1A, the plasma trap 9 is defined by three

faces, that is, an inner face, an upper face, and an outer face of the counter electrode 5. In Fig. 3, the plasma trap 9 is defined by three faces, that is, an inner face, an upper face, and an outer face of the insulating ring 11.

5 In Fig. 4, the plasma trap 9 is defined by three faces, that is, an inner face, an upper face, and an outer face of the upper wall 1a of the vacuum chamber 1. In Fig. 5, the plasma trap 9 is defined by an inner face of the counter electrode 5 and an upper face and an outer face of the
10 insulating ring 11. In Fig. 6, the plasma trap 9 is defined by an inner face and an upper face of the counter electrode 5 and an outer face of the insulating ring 11 and the upper wall 1a of the vacuum chamber 1. In Fig. 7, the plasma trap 9 is defined by an inner face of the insulating
15 ring 11 and an upper face and an outer face of the upper wall 1a of the vacuum chamber 1.

Next, a seventh embodiment of the present invention is described with reference to Figs. 8 and 9.

Fig. 8 shows a sectional view of a plasma
20 processing apparatus employed in the seventh embodiment of the present invention. Referring to Fig. 8, while interior of a vacuum chamber 1 is maintained to a specified pressure by introducing a specified gas from a gas supply unit 2 into the vacuum chamber 1 and simultaneously performing
25 evacuation by a pump 3 as an evacuating device, a high-

frequency power of 100 MHz is supplied to a spiral antenna 13 by an antenna-use-high-frequency power supply 12, and electromagnetic waves are radiated into the vacuum chamber 1 via a dielectric window 14 provided opposite to the substrate 7 placed on the substrate electrode 6. Then, plasma is generated in the vacuum chamber 1, where plasma processing such as etching, deposition, and surface reforming can be carried out on the substrate 7. Besides, a substrate-electrode-use-high-frequency power supply 8 for supplying high-frequency power to the substrate electrode 6 is provided, so that ion energy that reaches the substrate 7 can be controlled. Also, an annular, groove-like plasma trap 9 provided opposite to the substrate 7 makes it possible to process the substrate 7 while the plasma distribution on the substrate 7 is controlled. The plasma trap 9 is provided in the dielectric window 14 to be defined by an inner, an upper, and an outer faces of the dielectric window 14. Out of surfaces of the vacuum chamber 1 opposing to the substrate 7, a portion 10 (cross hatched portion) surrounded by the plasma trap 9 has an area 0.8 time that of the substrate 7, as one example. Also, the groove width of the plasma trap 9 is 10 mm, and the groove depth of the plasma 9 is 15 mm, as one example.

Fig. 9 shows measuring results of ion saturation current density at a position 20 mm just above the

substrate 7. Conditions for plasma generation are gas type of Cl_2 and gas flow rate of 100 sccm, a pressure of 1 Pa, and a high-frequency power of 2 kW, as one example. It can be understood from Fig. 9 that the tendency that plasma would be richer in peripheral regions as shown in Fig. 18 is suppressed, and that uniform plasma is generated.

The reason why the uniformity of plasma is improved like this as compared with the plasma processing apparatus shown in Fig. 16 of the prior art example could be considered as follows. Electromagnetic waves radiated from the spiral antenna 13 are intensified by the plasma trap 9. Also, since plasma of low electron temperature tends to cause hollow cathode discharge, high density plasma (hollow cathode discharge) is more likely to be generated by the plasma trap 9 surrounded by the solid surfaces. Accordingly, in the vacuum chamber 1, plasma density becomes the highest at the plasma trap 9, and through transport of plasma to vicinities of the substrate 7 by diffusion, uniform plasma can be obtained.

The seventh embodiment of the present invention has been described above on the case where the plasma trap 9 is provided in the dielectric window 14. However, the plasma trap 9 may also be provided outside the dielectric window 14 so as to be defined by three faces, that is, an inner face, an upper face, and an outer face of the upper

wall 1a of the vacuum chamber 1 as shown in an eighth embodiment of Fig. 10. Further, the plasma trap 9 may be provided between the vacuum chamber 1 and the dielectric window 14 so as to be defined by three faces, that is, an inner face of the dielectric window 14, an upper face and an outer face of the upper wall 1a of the vacuum chamber 1 as shown in a ninth embodiment of Fig. 11.

The foregoing embodiments of the present invention as described above are given only by way of example as part of many variations of the configuration of the vacuum chamber 1, the configuration and arrangement of the counter electrode 6 or antenna 13, the configuration and arrangement of the dielectric 14, and the configuration and arrangement of the plasma trap 9, within the application scope of the present invention. It is needless to say that the present invention may be applied in other various ways besides the examples given above. For example, whereas the foregoing embodiments have been described on the case where the counter electrode 6 is circular shaped, the counter electrode may also be formed in a polygonal, elliptical, or other shape. Also, whereas each of the foregoing cases has been that the antenna 13 is a spiral shaped, the antenna may be formed in a flat-plate, spoke, or other shape. Otherwise, the present invention may also be applied to a surface-wave plasma processing apparatus

having a cavity resonator 15, as shown in Fig. 12, where the cavity resonator 15 is regarded as an antenna. Furthermore, the present invention may be applied to a surface-wave plasma processing apparatus having a cavity resonator 15 and a slot antenna 16, as shown in Fig. 13.

The foregoing embodiments of the present invention have been described on the case where the plasma trap 9 is annular shaped. However, the plasma trap 9 may also be formed into a polygonal, elliptical, or other shape in accordance with the configuration of the substrate 7. Otherwise, the plasma trap 9 may be formed into a shape that is not a closed annular shape but a divisional, yet generally annular shape as shown by the plan view of Fig. 14. The above various kinds of the arrangement of the plasma trap 9 in Figs. 8, 10, and 11 etc. can be applied to the apparatus of Figs. 12 and 13.

Further, whereas the first or seventh embodiment of the present invention has been described on the case where a high-frequency power of 100 MHz is supplied to the counter electrode 6 or antenna 13, the frequency is not limited to this and the present invention is effective for plasma processing method and apparatus using frequencies of 50 MHz to 3 GHz.

Also, each of the first to seventh embodiments of the present invention has been described on the case where,

out of surfaces forming the inner wall surfaces of the vacuum chamber 1 and opposing the substrate 7, the area of the portion surrounded by the plasma trap 9 is 0.8 time the area of the substrate 7. However, it is desirable that the area of this portion be 0.5 - 2.5 times the area of the substrate 7. If the area of this portion is less than 0.5 time the area of the substrate 7, it is difficult to obtain uniform plasma in vicinities of the substrate 7 even with a sufficient distance between the substrate 7 and the plasma trap 9. Also, if the area of this portion is over 2.5 times the area of the substrate 7, it is necessary to keep an extremely large distance between the substrate 7 and the plasma trap 9 in order to obtain uniform plasma in vicinities of the substrate 7. This, undesirably, would cause the apparatus to be increased in size, and excessive burden to be imposed on the pump 3 to hold the interior of the vacuum chamber 1 at a low pressure. For example, when the substrate has a diameter of 300 mm and the plasma trap has a diameter of 200 mm, the area of this portion surrounded by the plasma trap is 0.5 times the area of the substrate. When the substrate has a diameter of 300 mm and the plasma trap has a diameter of 300 mm, the area of this portion surrounded by the plasma trap is 2.5 times the area of the substrate.

Also, each of the first to seventh embodiments of

the present invention has been described on the case where the groove width of the plasma trap 9 is 10 mm. However, it is desirable that the groove width of the plasma trap 9 be within a range of 3 mm - 50 mm. If the groove width is less than 3 mm, or if over 50 mm, there is a possibility that hollow cathode discharge does not occur by the plasma trap 9.

Also, whereas the foregoing embodiments have been described on the case where the groove of the plasma trap 9 is rectangular section-shaped, the groove sectional shape may be U-shaped, V-shaped, or of a shape in combination of rectangular shape, U-shape, and V-shape.

Also, each of the first to seventh embodiments of the present invention has been described on the case where the groove depth of the plasma trap 9 is 15 mm. However, it is desirable that the groove depth of the plasma trap 9 be not less than 5 mm. If the groove depth is less than 5 mm, there is a possibility that hollow cathode discharge does not occur.

The plasma processing apparatus of the third embodiment in Figs. 4 and 10 may be applied in a case where the area surrounded by the plasma trap 9 is larger than the area of the substrate 7. In this case, it is suitable to use per-fluorocarbon gas such as CF_4 gas, C_2F_6 gas, C_4F_8 gas, C_5F_8 gas, etc. or hydro-fluorocarbon such as CHF_3 gas, CH_2F_2 ,

etc.

On the other hand, a plasma processing apparatus of a modification of the third embodiment in Fig. 27 and a plasma processing apparatus of a modification of the eighth embodiment in Fig. 28 may be applied in a case where the area surrounded by the plasma trap 9 is not larger than the area of the substrate 7. In this case, it is suitable to use Boron-based gas such as HBr gas, or chlorine-based gas such as Cl_2 gas, BCl_3 gas, HCl gas etc.

Please note that although it is described as one example that the using gas is applied depending on the area surrounded by the plasma trap, the optimum selection of the using gas is not limited to this, but the optimum condition can be determined while referring to pressure, power, mixed gas, and the like because the optimum selection of the using gas depends on the conditions such as pressure, power, mixed gas, and the like.

Also, the foregoing embodiments of the present invention have been described on the case where DC magnetic fields are absent in the vacuum chamber 1. However, the present invention is also effective for cases where such large DC magnetic fields as to allow high-frequency power to penetrate into the plasma are absent, for example, a case where small DC magnetic fields on the order of several tens gauss are used for improvement in ignitability. Yet,

the present invention is particularly effective for cases where DC magnetic fields are absent in the vacuum chamber 1.

As apparent from the above description, the plasma processing method of the present invention for
5 generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode within the vacuum chamber, the method comprises: generating the plasma by supplying a high-frequency power having a frequency of 50 MHz to 3 GHz to a counter electrode provided opposite to
10 the substrate while interior of the vacuum chamber is controlled to a specified pressure by introducing gas into the vacuum chamber and, simultaneously therewith, evacuating the interior of the vacuum chamber; and processing the substrate by using the generated plasma
15 while plasma distribution of the plasma on the substrate is controlled by an annular, groove-like plasma trap provided opposite to the substrate. Thus, because the substrate is processed while the plasma distribution on the substrate is controlled by the annular, groove-like plasma trap provided
20 opposite to the substrate, uniform plasma can be generated so that the substrate can be uniformly processed.

Also, the plasma processing method of the present invention for generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode
25 within the vacuum chamber, the method comprises: generating

the plasma by radiating electromagnetic waves into the vacuum chamber via a dielectric window provided opposite to the substrate by supplying a high-frequency power having a frequency of 50 MHz to 3 GHz to an antenna while interior of the vacuum chamber is controlled to a specified pressure by introducing gas into the vacuum chamber and, simultaneously therewith, evacuating the interior of the vacuum chamber; and processing the substrate by using the generated plasma while plasma distribution of the plasma on the substrate is controlled by an annular, groove-like plasma trap provided opposite to the substrate. In this method, if the substrate is processed while the plasma distribution on the substrate is controlled by the annular, groove-like plasma trap provided opposite to the substrate, uniform plasma can be generated so that the substrate can be uniformly processed.

Also, the plasma processing apparatus of the present invention comprises: a vacuum chamber; a gas supply unit for supplying gas into the vacuum chamber; an evacuating device for evacuating interior of the vacuum chamber; a substrate electrode for placing thereon a substrate within the vacuum chamber; a counter electrode provided opposite to the substrate electrode; high-frequency power supply capable of supplying a high-frequency power having a frequency of 50 MHz to 3 GHz to the counter

electrode; and an annular, groove-like plasma trap provided opposite to the substrate. Thus, uniform plasma can be generated so that the substrate can be uniformly processed.

Also, the plasma processing apparatus of the
5 present invention comprises: a vacuum chamber; a gas supply unit for supplying gas into the vacuum chamber; an evacuating device for evacuating interior of the vacuum chamber; a substrate electrode for placing thereon a substrate within the vacuum chamber; a dielectric window
10 provided opposite to the substrate electrode; an antenna for radiating electromagnetic waves into the vacuum chamber via the dielectric window; high-frequency power supply capable of supplying a high-frequency power having a frequency of 50 MHz to 3 GHz to the antenna; and an annular, groove-like
15 plasma trap provided opposite to the substrate. Thus, uniform plasma can be generated so that the substrate can be uniformly processed.

Now, a tenth embodiment of the present invention is described below with reference to Figs. 19 and 20.

20 Fig. 19 shows a sectional view of a plasma processing apparatus employed in the tenth embodiment of the present invention. Referring to Fig. 19, while interior of a vacuum chamber 101 is maintained to a specified pressure by introducing a specified gas from a
25 gas supply unit 102 into the vacuum chamber 101 and

simultaneously performing evacuation by a pump 103 as an evacuating device, a high-frequency power of 100 MHz is supplied to a counter electrode 107 by a counter-electrode-use-high-frequency power supply 104 via a matching box 105 and a high-frequency coupling device (mount) 106. Then, plasma is generated in the vacuum chamber 101, where plasma processing such as etching, deposition, and surface reforming can be carried out on a substrate 109 placed on a substrate electrode 108. A substrate-electrode-use-high-frequency power supply 110 for supplying high-frequency power to the substrate electrode 108 is also provided, so that ion energy that reaches the substrate 109 can be controlled. In addition, the counter electrode 107 is insulated from the vacuum chamber 101 by an insulating ring 111.

The matching box 105, which is used to take impedance matching in supplying high-frequency power to the counter electrode 107 as a load, comprises a high-frequency input terminal 112, a first variable capacitor 113, a high-frequency output terminal 114, a second variable capacitor 115, a first motor 116, a second motor 117, and a motor control circuit 118. One end of the first variable capacitor 113 is connected to the high-frequency input terminal 112, the other end being connected to the matching box casing 105a, and one end of the second variable

capacitor 115 is connected to the high-frequency input terminal 112, the other end being connected to the high-frequency output terminal 114. Also, a straight line forming the center axis of the second variable capacitor 115, a straight line forming the center axis of the high-frequency output terminal 114, a straight line forming the center axis of the high-frequency coupling device (mount) 106, a straight line forming the center axis of the counter electrode 107, and a straight line forming the center axis of the substrate 109 are arranged so as to be generally coincident together. Also, the first variable capacitor 113 and the second variable capacitor 115 are so arranged that the straight line forming the center axis of the second variable capacitor 115 and a straight line forming the center axis of the first variable capacitor 113 are generally coincident with each other. Further, a substantial distance 19 from the other end of the second variable capacitor 115 to the counter electrode 107 is $1/15$ (20 cm) of the wavelength (3 m) of the high-frequency power, as one example.

Fig. 20 shows results of measuring ion saturation current density at a position 20 mm just above the substrate 109. Conditions for plasma generation are gas type of Cl_2 and gas flow rate of 100 sccm, a pressure of 2 Pa, and a high-frequency power of 1 kW, as one example.

Also, Fig. 19 shows the measuring position in Fig. 20. It can be understood from Fig. 20 that nonuniformity of plasma as shown in Fig. 25, where plasma density is higher on one side of the measuring position, cannot be seen.

5 The reason why the uniformity of plasma is improved like this as compared with the plasma processing apparatus shown in Fig. 24 of the prior art example could be considered as follows. In the case where a high-frequency power of 50 MHz or higher is used, there develops
10 a potential distribution in the counter electrode 107 under the effect of the arrangement of the second variable capacitor 115 within the matching box 105. However, in the tenth embodiment of the present invention, the potential distribution developed on the counter electrode 107 becomes
15 concentric because of the arrangement that a straight line forming the center axis of the second variable capacitor 115, a straight line forming the center axis of the high-frequency output terminal 114, a straight line forming the center axis of the high-frequency coupling device (mount)
20 106, a straight line forming the center axis of the counter electrode 107, and a straight line forming the center axis of the substrate 109 are generally coincident together. As a result, the electric fields within the vacuum chamber 101 also become concentric so that the uniformity of plasma can
25 be improved.

The foregoing tenth embodiment of the present invention has been described on the case where the counter electrode 107 is used to generate plasma. However, the present invention is also effective for cases where a spiral antenna 120 is used as in an eleventh embodiment of the present invention shown in Fig. 21. In addition, in the eleventh embodiment of the present invention shown in Fig. 21, a dielectric window 121 is used.

Also, the foregoing tenth and eleventh embodiments of the present invention are given only by way of example as part of many variations of the configuration of the vacuum chamber 101, the configuration and arrangement of the counter electrode 107 or antenna 120, the configuration and arrangement of the dielectric 121, and the like within the application scope of the present invention. It is needless to say that the present invention may be applied in other various ways besides the examples given above. For example, whereas the tenth embodiment of the present invention has been described on a case where the counter electrode 107 is circular shaped, the counter electrode may also be formed in a polygonal, elliptical, or other shape. Also, whereas the foregoing case has been that the antenna 120 is a spiral shaped, the antenna may be formed in a flat-plate, spoke, or other shape.

The foregoing tenth and eleventh embodiments of the present invention have been described on the case where the high-frequency power of 100 MHz is supplied to the counter electrode 107 or antenna 120, the frequency is not limited to this and the present invention is effective for cases where frequencies of 50 MHz to 300 MHz are used. If the frequency is lower than 50 MHz, the uniformity of plasma can be easily obtained even without applying the present invention. Also, if the frequency is higher than 300 MHz, it is difficult to take impedance matching by using two variable capacitors, giving rise to a need of taking impedance matching by stubs.

Also, the tenth and eleventh embodiments of the present invention have been described on a case where the first variable capacitor and the second variable capacitor are so arranged that the straight line forming the center axis of the second variable capacitor and the straight line forming the center axis of the first variable capacitor are generally coincident with each other. However, because the potential distribution developed to the counter electrode 107 is affected primarily by the arrangement of the second variable capacitor, the uniformity of plasma is greatly improved, as compared with the prior art, also when the straight line forming the center axis of the second variable capacitor 115 and the straight line forming the

center axis of the first variable capacitor 113 are not coincident with each other as in a twelfth embodiment of the present invention shown in Fig. 22. Such a constitution as shown in Fig. 22 is effective for cases
5 where the matching box needs to be downsized, the constitution being included in the application scope of the present invention.

Also, the twelfth embodiment of the present invention has been described on the case where the matching
10 box has variable capacitors by way of example. However, the present invention produces similar effects also with a matching box having reactive elements such as variable inductors, fixed capacitors, or fixed inductors.

Also, whereas the twelfth embodiment has been
15 described on the case where the other end of the second variable capacitor 115 and the high-frequency output terminal are provided as separate members. However, the high-frequency output terminal 114 may be provided as the other end of the second variable capacitor 115 itself, as
20 in a thirteenth embodiment of the present invention shown in Fig. 23.

Also, the tenth embodiment of the present invention has been described on the case where the substantial distance from the other end of the second
25 variable capacitor 115 to the counter electrode 107 is $1/15$

of the wavelength of the high-frequency power. It is desirable that the substantial distance from the other end of the second variable capacitor 115 to the counter electrode 107 or antenna 120 be $1/10$ or less of the wavelength of the high-frequency power. If the substantial distance from the other end of the second variable capacitor 115 to the counter electrode 107 or antenna is larger than $1/10$ of the wavelength of the high-frequency power, the inductance from the other end of the second variable capacitor 115 to the counter electrode 107 or antenna becomes too large, making it difficult to take impedance matching with two variable capacitors.

In the foregoing embodiments, any one of the embodiments can be combined with any one of the embodiments. For example, Fig. 29 is a sectional view showing the constitution of a plasma processing apparatus where the plasma processing apparatus in the tenth embodiment of the present invention in Fig. 19 and the plasma processing apparatus in the modification of the third embodiment of the present invention in Fig. 27 are combined with each other. Fig. 30 is a sectional view showing the constitution of a plasma processing apparatus where the plasma processing apparatus in the eleventh embodiment of the present invention in Fig. 21 and the plasma processing apparatus in the modification of the eighth embodiment of

the present invention in Fig. 28 are combined with each other. Such a combination can obtain the both of the effects of the combined embodiments.

As apparent from the above description, the
5 matching box of the present invention for use in a plasma processing apparatus and for taking impedance matching in supplying high-frequency power to a load, the matching box comprises: a high-frequency input terminal; a first
10 reactive element having one end connected to the high-frequency input terminal and the other end connected to a matching box casing; a high-frequency output terminal; and a second reactive element having one end connected to the high-frequency input terminal and the other end connected to the high-frequency output terminal, wherein the second
15 reactive element and the high-frequency output terminal are so arranged that the second reactive element is located on a straight line passing through a center axis of the high-frequency output terminal. Thus, uniform plasma can be generated so that the substrate can be uniformly processed.

20 Also, the matching box of the present invention for use in a plasma processing apparatus and for taking impedance matching in supplying high-frequency power to a load, the matching box comprises: a high-frequency input terminal; a first variable capacitor having one end
25 connected to the high-frequency input terminal and the

other end connected to a matching box casing; a high-frequency output terminal; and a second variable capacitor having one end connected to the high-frequency input terminal and the other end connected to the high-frequency output terminal, wherein the second variable capacitor and the high-frequency output terminal are so arranged that the second variable capacitor is located on a straight line passing through a center axis of the high-frequency output terminal. Thus, uniform plasma can be generated so that the substrate can be uniformly processed.

Also, the plasma processing method of the present invention for generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode within the vacuum chamber, the method comprises: so arranging a straight line passing through a center axis of the high-frequency coupling device, a straight line passing through a center axis of the counter electrode or antenna, and a straight line passing through a center axis of the substrate as to be generally coincident together; controlling interior of the vacuum chamber to a specified pressure by introducing a gas into the vacuum chamber and, simultaneously therewith, exhausting the interior of the vacuum chamber; generating the plasma by applying a high-frequency power having a frequency of 50 MHz to 300 MHz to a counter electrode or antenna provided opposite to the

substrate via the matching box as defined in Claim 28 and a high-frequency coupling device provided to connect a high-frequency output terminal of the matching box and the counter electrode or antenna to each other: and processing the substrate by using the generated plasma. Thus, uniform plasma can be generated so that the substrate can be uniformly processed.

Also, the plasma processing method of the present invention for generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode within the vacuum chamber, the method comprises: so arranging a straight line passing through a center axis of the high-frequency coupling device, a straight line passing through a center axis of the counter electrode or antenna, and a straight line passing through a center axis of the substrate as to be generally coincident together; controlling interior of the vacuum chamber to a specified pressure by introducing a gas into the vacuum chamber and, simultaneously therewith, exhausting the interior of the vacuum chamber; generating the plasma by applying a high-frequency power having a frequency of 50 MHz to 300 MHz to a counter electrode or antenna provided opposite to the substrate via the matching box as defined in Claim 33 and a high-frequency coupling device provided to connect a high-frequency output terminal of the matching box and the

counter electrode or antenna to each other; and processing the substrate by using the generated plasma. Thus, uniform plasma can be generated so that the substrate can be uniformly processed.

5 Also, the plasma processing apparatus comprises:
a vacuum chamber; a gas supply unit for supplying gas into
the vacuum chamber; an evacuating device for evacuating
interior of the vacuum chamber; a substrate electrode for
placing thereon a substrate within the vacuum chamber; a
10 counter electrode or an antenna provided opposite to the
substrate electrode; high-frequency power supply capable of
supplying a high-frequency power having a frequency of 50
MHz to 300 MHz to the counter electrode or antenna; the
matching box as defined in the 28th aspect; and a high-
15 frequency coupling device for connecting the high-frequency
output terminal of the matching box and the counter
electrode or antenna to each other, wherein a straight line
passing through a center axis of the high-frequency
coupling device, a straight line passing through a center
20 axis of the counter electrode or antenna, and a straight
line passing through a center axis of the substrate are so
arranged as to be generally coincident together. Thus,
uniform plasma can be generated so that the substrate can
be uniformly processed.

25 Also, the plasma processing apparatus comprises:

a vacuum chamber; a gas supply unit for supplying gas into the vacuum chamber; an evacuating device for evacuating interior of the vacuum chamber; a substrate electrode for placing thereon a substrate within the vacuum chamber; a counter electrode or an antenna provided opposite to the substrate electrode; high-frequency power supply capable of supplying a high-frequency power having a frequency of 50 MHz to 300 MHz to the counter electrode or antenna; the matching box as defined in the 33rd aspect; and a high-frequency coupling device for connecting the high-frequency output terminal of the matching box and the counter electrode or antenna to each other, wherein a straight line passing through a center axis of the high-frequency coupling device, a straight line passing through a center axis of the counter electrode or antenna, and a straight line passing through a center axis of the substrate are so arranged as to be generally coincident together. Thus, uniform plasma can be generated so that the substrate can be uniformly processed.

Although the present invention has been fully described in connection with the preferred embodiments thereof with reference to the accompanying drawings, it is to be noted that various changes and modifications are apparent to those skilled in the art. Such changes and modifications are to be understood as included within the

scope of the present invention as defined by the appended claims unless they depart therefrom.

[illegible]

WHAT IS CLAIMED IS:

1. A plasma processing method for generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode within the vacuum chamber, the method comprising:

generating the plasma by supplying a high-frequency power having a frequency of 50 MHz to 3 GHz to a counter electrode provided opposite to the substrate while interior of the vacuum chamber is controlled to a specified pressure by introducing gas into the vacuum chamber and, simultaneously therewith, evacuating the interior of the vacuum chamber; and

processing the substrate by using the generated plasma while plasma distribution of the plasma on the substrate is controlled by an annular, groove-like plasma trap provided opposite to the substrate.

2. A plasma processing method for generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode within the vacuum chamber, the method comprising:

generating the plasma by radiating electromagnetic waves into the vacuum chamber via a dielectric window provided opposite to the substrate by supplying a high-frequency power having a frequency of 50 MHz to 3 GHz to an antenna while interior of the vacuum chamber is controlled

to a specified pressure by introducing gas into the vacuum chamber and, simultaneously therewith, evacuating the interior of the vacuum chamber; and

processing the substrate by using the generated
5 plasma while plasma distribution of the plasma on the substrate is controlled by an annular, groove-like plasma trap provided opposite to the substrate.

3. A plasma processing method according to Claim 1,
wherein the substrate is processed while a portion
10 surrounded by the plasma trap out of a surface forming an inner wall surface of the vacuum chamber and opposing the substrate has an area 0.5 to 2.5 times that of the substrate.

4. A plasma processing method according to Claim 1,
wherein the substrate is processed while the plasma trap
15 has a groove width of 3 mm to 50 mm.

5. A plasma processing method according to Claim 1,
wherein the substrate is processed while the plasma has a groove depth of not less than 5 mm.

6. A plasma processing method according to Claim 1,
20 wherein the substrate is processed while the plasma trap is provided in the counter electrode.

7. A plasma processing method according to Claim 1,
wherein the plasma is generated while the plasma trap is provided outside an insulating ring for insulating the
25 vacuum chamber and the counter electrode from each other.

8. A plasma processing method according to Claim 1, wherein the plasma is generated while the plasma trap is provided between the counter electrode and an insulating ring for insulating the vacuum chamber and the counter electrode from each other.

9. A plasma processing method according to Claim 1, wherein the plasma is generated while the plasma trap is provided between the vacuum chamber and an insulating ring for insulating the vacuum chamber and the counter electrode from each other.

10. A plasma processing method according to Claim 2, wherein the plasma is generated while the plasma trap is provided in the dielectric window.

11. A plasma processing method according to Claim 2, wherein the plasma is generated while the plasma trap is provided outside the dielectric window.

12. A plasma processing method according to Claim 2, wherein the plasma is generated while the plasma trap is provided between the vacuum chamber and the dielectric window.

13. A plasma processing method according to Claim 1, wherein the plasma is generated while DC magnetic fields are absent within the vacuum chamber.

14. A plasma processing apparatus comprising:

a vacuum chamber;

-- a gas supply unit for supplying gas into the vacuum chamber;

an evacuating device for evacuating interior of the vacuum chamber;

5 a substrate electrode for placing thereon a substrate within the vacuum chamber;

a counter electrode provided opposite to the substrate electrode;

high-frequency power supply capable of supplying
10 a high-frequency power having a frequency of 50 MHz to 3 GHz to the counter electrode; and

an annular, groove-like plasma trap provided opposite to the substrate.

15. A plasma processing apparatus comprising:

15 a vacuum chamber;

a gas supply unit for supplying gas into the vacuum chamber;

an evacuating device for evacuating interior of the vacuum chamber;

20 a substrate electrode for placing thereon a substrate within the vacuum chamber;

a dielectric window provided opposite to the substrate electrode;

an antenna for radiating electromagnetic waves
25 into the vacuum chamber via the dielectric window;

high-frequency power supply capable of supplying a high-frequency power having a frequency of 50 MHz to 3 GHz to the antenna; and

an annular, groove-like plasma trap provided
5 opposite to the substrate.

16. A plasma processing apparatus according to Claim 14, wherein a portion surrounded by the plasma trap out of a surface forming an inner wall surface of the vacuum chamber and opposing the substrate has an area 0.5 to 2.5 times that
10 of the substrate.

17. A plasma processing apparatus according to Claim 14, wherein the plasma trap has a groove width of 3 mm to 50 mm.

18. A plasma processing apparatus according to Claim
15 14 or 15, wherein the plasma has a groove depth of not less than 5 mm.

19. A plasma processing apparatus according to Claim 14, wherein the plasma trap is provided in the counter electrode.

20 20. A plasma processing apparatus according to Claim 14, wherein the plasma trap is provided in an insulating ring for insulating the vacuum chamber and the counter electrode from each other.

21. A plasma processing apparatus according to Claim
25 14, wherein the plasma trap is provided outside an

insulating ring for insulating the vacuum chamber and the counter electrode from each other.

22. A plasma processing apparatus according to Claim 14, wherein the plasma trap is provided between the counter electrode and an insulating ring for insulating the vacuum chamber and the counter electrode from each other.

23. A plasma processing apparatus according to Claim 14, wherein the plasma trap is provided between the vacuum chamber and an insulating ring for insulating the vacuum chamber and the counter electrode from each other.

24. A plasma processing apparatus according to Claim 15, wherein the plasma trap is provided in the dielectric window.

25. A plasma processing apparatus according to Claim 15, wherein the plasma trap is provided outside the dielectric window.

26. A plasma processing apparatus according to Claim 15, wherein the plasma trap is provided between the vacuum chamber and the dielectric window.

27. A plasma processing apparatus according to Claim 14, wherein no coil or permanent magnet for applying DC magnetic fields is provided within the vacuum chamber.

28. A plasma processing apparatus according to Claim 1, further comprising a matching box for use in the plasma processing apparatus and for taking impedance matching in

supplying high-frequency power to a load, the matching box comprising:

a high-frequency input terminal;

5 a first reactive element having one end connected to the high-frequency input terminal and the other end connected to a matching box casing;

a high-frequency output terminal; and

10 a second reactive element having one end connected to the high-frequency input terminal and the other end connected to the high-frequency output terminal,

wherein the second reactive element and the high-frequency output terminal are so arranged that the second reactive element is located on a straight line passing through a center axis of the high-frequency output terminal.

15 29. A plasma processing apparatus according to Claim 28, wherein the first reactive element and the second reactive element are capacitors, respectively.

30. A matching box for use in a plasma processing apparatus and for taking impedance matching in supplying
20 high-frequency power to a load, the matching box comprising:

a high-frequency input terminal;

25 a first reactive element having one end connected to the high-frequency input terminal and the other end connected to a matching box casing;

a high-frequency output terminal; and
a second reactive element having one end
connected to the high-frequency input terminal and the
other end connected to the high-frequency output terminal,

5 wherein the second reactive element and the high-
frequency output terminal are so arranged that the second
reactive element is located on a straight line passing
through a center axis of the high-frequency output terminal.

31. A matching box for a plasma processing apparatus
10 according to Claim 30, wherein the second reactive element
and the high-frequency output terminal are so arranged that
a straight line passing through a center axis of the second
reactive element and a straight line passing through the
center axis of the high-frequency output terminal are
15 generally coincident with each other.

32. A matching box for a plasma processing apparatus
according to Claim 30, wherein the first reactive element
and the second reactive element are capacitors,
respectively.

20 33. A matching box for a plasma processing apparatus
according to Claim 30, wherein the first reactive element
and the second reactive element are so arranged that a
straight line passing through a center axis of the second
reactive element and a straight line passing through a
25 center axis of the first reactive element are generally

coincident with each other.

34. A matching box for a plasma processing apparatus according to Claim 30, wherein the high-frequency output terminal is the other end itself of the second reactive
5 element.

35. A plasma processing method for generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode within the vacuum chamber, the method comprising:

10 so arranging a straight line passing through a center axis of the high-frequency coupling device, a straight line passing through a center axis of the counter electrode or antenna, and a straight line passing through a center axis of the substrate as to be generally coincident
15 together;

controlling interior of the vacuum chamber to a specified pressure by introducing a gas into the vacuum chamber and, simultaneously therewith, exhausting the interior of the vacuum chamber;

20 generating the plasma by applying a high-frequency power having a frequency of 50 MHz to 300 MHz to a counter electrode or antenna provided opposite to the substrate via the matching box as defined in Claim 30 and a high-frequency coupling device provided to connect a high-
25 frequency output terminal of the matching box and the

counter electrode or antenna to each other: and

processing the substrate by using the generated plasma.

36. A plasma processing method according to Claim 35,
5 further comprising: before controlling the interior of the vacuum chamber to the specified pressure,

so arranging a straight line passing through a center axis of the high-frequency output terminal and a straight line passing through the center axis of the high-frequency coupling device as to be generally coincident with each other,
10

wherein the plasma is generated with the straight line passing through the center axis of the high-frequency output terminal and the straight line passing through the center axis of the high-frequency coupling device being
15 generally coincident with each other.

37. A plasma processing method according to Claim 35, further comprising: before controlling the interior of the vacuum chamber to the specified pressure,

20 so arranging the first reactive element and the second reactive element that a straight line passing through a center axis of the second reactive element and a straight line passing through a center axis of the first reactive element are generally coincident with each other,

25 wherein the plasma is generated with the straight

line passing through the center axis of the second reactive element and the straight line passing through the center axis of the first reactive element being generally coincident with each other.

5 38. A plasma processing method according to Claim 35, comprising: before controlling the interior of the vacuum chamber to the specified pressure,

 arranging the high-frequency output terminal so as to be the other end itself of the second reactive
10 element,

 wherein the plasma is generated with the high-frequency output terminal being the other end itself of the second reactive element.

 39. A plasma processing method according to Claim 35,
15 comprising: before controlling the interior of the vacuum chamber to the specified pressure,

 arranging substantial distance from the other end of the second reactive element to the counter electrode or antenna to be not more than $1/10$ of wavelength of the high-
20 frequency power,

 wherein the plasma is generated with the substantial distance from the other end of the second reactive element to the counter electrode or antenna being not more than $1/10$ of wavelength of the high-frequency
25 power.

40. A plasma processing method for generating plasma within a vacuum chamber and processing a substrate placed on a substrate electrode within the vacuum chamber, the method comprising:

5 so arranging a straight line passing through a center axis of the high-frequency coupling device, a straight line passing through a center axis of the counter electrode or antenna, and a straight line passing through a center axis of the substrate as to be generally coincident
10 together;

 controlling interior of the vacuum chamber to a specified pressure by introducing a gas into the vacuum chamber and, simultaneously therewith, exhausting the interior of the vacuum chamber;

15 generating the plasma by applying a high-frequency power having a frequency of 50 MHz to 300 MHz to a counter electrode or antenna provided opposite to the substrate via the matching box as defined in Claim 30 and a high-frequency coupling device provided to connect a high-
20 frequency output terminal of the matching box and the counter electrode or antenna to each other; and

 processing the substrate by using the generated plasma.

41. A plasma processing method according to Claim 40,
25 further comprising: before controlling the interior of the

vacuum chamber to the specified pressure,

so arranging a straight line passing through a center axis of the high-frequency output terminal and a straight line passing through the center axis of the high-frequency coupling device as to be generally coincident with each other,

wherein the plasma is generated with the straight line passing through the center axis of the high-frequency output terminal and the straight line passing through the center axis of the high-frequency coupling device being generally coincident with each other.

42. A plasma processing method according to Claim 40, further comprising: before controlling the interior of the vacuum chamber to the specified pressure,

so arranging the first variable capacitor and the second variable capacitor that a straight line passing through a center axis of the second variable capacitor and a straight line passing through a center axis of the first variable capacitor are generally coincident with each other,

wherein the plasma is generated with the straight line passing through the center axis of the second variable capacitor and the straight line passing through the center axis of the first variable capacitor being generally coincident with each other.

43. A plasma processing method according to Claim 40,

comprising: before controlling the interior of the vacuum chamber to the specified pressure,

arranging the high-frequency output terminal so as to be the other end itself of the second reactive element,

wherein the plasma is generated with the high-frequency output terminal being the other end itself of the second variable capacitor.

44. A plasma processing method according to Claim 40, further comprising: before controlling the interior of the vacuum chamber to the specified pressure,

arranging substantial distance from the other end of the second variable capacitor to the counter electrode or antenna to be not more than $1/10$ of wavelength of the high-frequency power,

wherein the plasma is generated with the substantial distance from the other end of the second variable capacitor to the counter electrode or antenna to be not more than $1/10$ of wavelength of the high-frequency power.

45. A plasma processing apparatus comprising:

a vacuum chamber;

a gas supply unit for supplying gas into the vacuum chamber;

an evacuating device for evacuating interior of

the vacuum chamber;

a substrate electrode for placing thereon a substrate within the vacuum chamber;

a counter electrode or an antenna provided
5 opposite to the substrate electrode;

high-frequency power supply capable of supplying a high-frequency power having a frequency of 50 MHz to 300 MHz to the counter electrode or antenna;

the matching box as defined in Claim 30; and

10 a high-frequency coupling device for connecting the high-frequency output terminal of the matching box and the counter electrode or antenna to each other,

wherein a straight line passing through a center axis of the high-frequency coupling device, a straight line
15 passing through a center axis of the counter electrode or antenna, and a straight line passing through a center axis of the substrate are so arranged as to be generally coincident together.

46. A plasma processing apparatus according to Claim
20 45, wherein a straight line passing through a center axis of the high-frequency output terminal and a straight line passing through the center axis of the high-frequency coupling device are so arranged as to be generally coincident with each other.

25 47. A plasma processing apparatus according to Claim

45, wherein the first reactive element and the second reactive element are so arranged that a straight line passing through a center axis of the second reactive element and a straight line passing through a center axis of the first reactive element are generally coincident with each other.

48. A plasma processing apparatus according to Claim 45, wherein the high-frequency output terminal is the other end itself of the second reactive element.

49. A plasma processing apparatus according to Claim 45, wherein substantial distance from the other end of the second reactive element to the counter electrode or antenna is not more than $1/10$ of wavelength of the high-frequency power.

50. A plasma processing apparatus comprising:

a vacuum chamber;

a gas supply unit for supplying gas into the vacuum chamber;

an evacuating device for evacuating interior of the vacuum chamber;

a substrate electrode for placing thereon a substrate within the vacuum chamber;

a counter electrode or an antenna provided opposite to the substrate electrode;

high-frequency power supply capable of supplying

a high-frequency power having a frequency of 50 MHz to 300 MHz to the counter electrode or antenna;

the matching box as defined in Claim 30; and

a high-frequency coupling device for connecting
5 the high-frequency output terminal of the matching box and the counter electrode or antenna to each other,

wherein a straight line passing through a center axis of the high-frequency coupling device, a straight line passing through a center axis of the counter electrode or antenna, and a straight line passing through a center axis of the substrate are so arranged as to be generally coincident together.
10

51. A plasma processing apparatus according to Claim 50, wherein the plasma is generated while the straight line
15 passing through the center axis of the high-frequency output terminal and the straight line passing through the center axis of the high-frequency coupling device are so arranged as to be generally coincident with each other.

52. A plasma processing apparatus according to Claim 50, wherein a first variable capacitor and a second variable capacitor are so arranged that a straight line passing through a center axis of the second variable capacitor and a straight line passing through a center axis of the first variable capacitor are generally coincident with each other.
20

53. A plasma processing apparatus according to Claim
25

50, wherein the high-frequency output terminal is the other end itself of the second variable capacitor.

54. A plasma processing apparatus according to Claim 50, wherein substantial distance from the other end of the second variable capacitor to the counter electrode or antenna is not more than $1/10$ of wavelength of the high-frequency power.

ABSTRACT OF THE DISCLOSURE

While interior of a vacuum chamber is maintained to a specified pressure by introducing a specified gas into the vacuum chamber having a plasma trap provided therein and, simultaneously therewith, performing evacuation by a pump as an evacuating device, a high-frequency power of 100 MHz is supplied to a counter electrode by counter-electrode use high-frequency power supply. Thus, uniform plasma is generated within the vacuum chamber, where plasma processing such as etching, deposition, and surface reforming can be carried out uniformly with a substrate placed on a substrate electrode.

Fig. 1A




Fig. 1B




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28





Fig. 30



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of :
Tomohiro OKUMURA et al. : **Attn: APPLICATION BRANCH**
Serial No. NEW : Docket No. 00177/530809
Filed February 23, 2000 :
**PLASMA PROCESSING METHOD AND
APPARATUS**

**COVER LETTER FOR APPLICATION FILED
WITHOUT EXECUTED DECLARATION**

Assistant Commissioner for Patents,
Washington, DC 20231

Sir:

The above-identified application has been submitted without an executed oath or declaration pursuant to 37 CFR 1.41(c).

It is respectfully requested that this application be assigned a serial number and awarded a filing date pursuant to 37 CFR 1.53.

A duly executed oath or declaration pursuant to 37 CFR 1.63 will be submitted after notification by the U.S. Patent and Trademark Office pursuant to 37 CFR 1.53(d).


A non-executed copy of the Declaration and Power of Attorney, containing the inventorship information, is attached. It is respectfully requested that all communications be directed to the firm indicated on the attached Declaration and Power of Attorney, namely:

WENDEROTH, LIND & PONACK, L.L.P.
2033 K Street, N.W., Suite 800
Washington, D.C. 20006

The required U.S. Patent and Trademark Office Filing Fee is submitted herewith.

Respectfully submitted,

Tomohiro OKUMURA et al.

By 

Charles R. Watts
Registration No. 33,142
Attorney for Applicants

CRW/asd
Washington, D.C.
Telephone (202) 721-8200
Facsimile (202) 721-8250
February 23, 2000

DECLARATION AND POWER OF ATTORNEY FOR U.S. PATENT APPLICATION

(X) Original () Supplemental () Substitute () PCT () DESIGN

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; that I verily believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Title: PLASMA PROCESSING METHOD AND APPARATUS

of which is described and claimed in:

() the attached specification, or

(X) the specification in application Serial No. _____, filed February 23, 2000, and with amendments through _____ (if applicable), or

() the specification in International Application No. _____, filed _____, and as amended on _____ (if applicable).

I hereby state that I have reviewed and understand the content of the above-identified specification, including the claims, as amended by any amendment(s) referred to above.

I acknowledge my duty to disclose to the Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I hereby claim priority benefits under Title 35, United States Code, §119 (and §172 if this application is for a Design) of any application(s) for patent or inventor's certificate listed below and have also identified below any application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

COUNTRY	APPLICATION NO.	DATE OF FILING	PRIORITY CLAIMED
Japan	11-044359	February 23, 1999	YES
Japan	11-046245	February 24, 1999	YES

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

APPLICATION SERIAL NO.	U.S. FILING DATE	STATUS: PATENTED, PENDING, ABANDONED

And I hereby appoint Michael R. Davis, Reg. No. 25,134; Matthew M. Jacob, Reg. No. 25,154; Jeffrey Noltan, Reg. No. 25,408; Warren M. Cheek, Jr., Reg. No. 33,367; Nils Pedersen, Reg. No. 33,145; and Charles R. Watts, Reg. No. 33,142, who together constitute the firm of WENDEROTH, LIND & PONACK, L.L.P., jointly and severally, attorneys to prosecute this application and to transact all business in the U.S. Patent and Trademark Office connected therewith.

I hereby authorize the U.S. attorneys named herein to accept and follow instructions from AOYAMA & PARTNERS as to any action to be taken in the U.S. Patent and Trademark Office regarding this application without direct communication between the U.S. attorneys and myself. In the event of a change in the persons from whom instructions may be taken, the U.S. attorneys named herein will be so notified by me.

Send Correspondence to

Direct Telephone Calls to:

WENDEROTH, LIND & PONACK, L.L.P.
2033 K Street, N.W., Suite 800
Washington, D.C. 20006

WENDEROTH, LIND & PONACK, L.L.P.
Area Code (202) 721-8200

Direct Facsimile Messages to:
Area Code (202) 721-8250

Full Name of First Inventor	FAMILY NAME OKUMURA	FIRST GIVEN NAME Tomohiro	SECOND GIVEN NAME
Residence & Citizenship	CITY Osaka-fu,	STATE OR COUNTRY Japan	COUNTRY OF CITIZENSHIP Japan
Post Office Address	ADDRESS 13-13-201, Suehiro-cho, Kadoma-shi, Osaka-fu, Japan	CITY	STATE OR COUNTRY ZIP CODE
Full Name of Second Inventor	FAMILY NAME HARAGUCHI	FIRST GIVEN NAME Hideo	SECOND GIVEN NAME
Residence & Citizenship	CITY Osaka-fu,	STATE OR COUNTRY Japan	COUNTRY OF CITIZENSHIP Japan
Post Office Address	ADDRESS 2-11-35, Ueno-higashi, Toyonaka-shi, Osaka-fu, Japan	CITY	STATE OR COUNTRY ZIP CODE
Full Name of Third Inventor	FAMILY NAME MATSUI	FIRST GIVEN NAME Takuya	SECOND GIVEN NAME
Residence & Citizenship	CITY Osaka-fu,	STATE OR COUNTRY Japan	COUNTRY OF CITIZENSHIP Japan
Post Office Address	ADDRESS 4-6-9, Ogawa, Matsubara-shi, Osaka-fu, Japan	CITY	STATE OR COUNTRY ZIP CODE
Full Name of Fourth Inventor	FAMILY NAME MATSUDA	FIRST GIVEN NAME Izuru	SECOND GIVEN NAME
Residence & Citizenship	CITY Osaka-fu,	STATE OR COUNTRY Japan	COUNTRY OF CITIZENSHIP Japan
Post Office Address	ADDRESS 2-3-207, Wakita-cho, Kadoma-shi, Osaka-fu, Japan	CITY	STATE OR COUNTRY ZIP CODE
Full Name of Fifth Inventor	FAMILY NAME MITSUHASHI	FIRST GIVEN NAME Akio	SECOND GIVEN NAME
Residence & Citizenship	CITY Osaka-fu,	STATE OR COUNTRY Japan	COUNTRY OF CITIZENSHIP Japan
Post Office Address	ADDRESS 2-1-7-311, Yamashiro-cho, Yao-shi, Osaka-fu, Japan	CITY	STATE OR COUNTRY ZIP CODE
Full Name of Sixth Inventor	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
Residence & Citizenship	CITY	STATE OR COUNTRY	COUNTRY OF CITIZENSHIP
Post Office Address	ADDRESS	CITY	STATE OR COUNTRY ZIP CODE

I further declare that all statements made herein of my own knowledge are true, and that all statements on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

1st Inventor	Tomohiro OKUMURA	Date	
2nd Inventor	Hideo HARAGUCHI	Date	
3rd Inventor	Takuya MATSUI	Date	
4th Inventor	Izuru MATSUDA	Date	
5th Inventor	Akio MITSUHASHI	Date	
6th Inventor		Date	

The above application may be more particularly identified as follows:

U.S. Application Serial No. _____ Filing Date February 23, 2000

Applicant Reference Number 530809 Atty Docket No. 00177/530809

Title of Invention PLASMA PROCESSING METHOD AND APPARATUS